



Pitch Range		Nominal Dimension		Range		
mm	In	mm	In	mm	In	
Over 6	Over 10	Over 30	Over 60	Over 100	Over 150	0.1/10
TO 10	TO 24	TO 10	TO 60	TO 100	TO 150	≤
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00
						±1.30
						±2*

8	Clamp	Copper alloy	Sn Plated
7	Spring	Stainless Steel	
6	Cover 2	PA66	UL94V-0
5	Side Housing 2	PA66	UL94V-0
4	Middle Housing 2	PA66	UL94V-0
3	Middle Housing 1	PA66	UL94V-0
2	Side Housing 1	PA66	UL94V-0
1	Cover 1	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
额定电压/电涌/Rated Voltage(V)/Current(A)		300/15/300/15	
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级		III/3	II/2
绝缘/Insulation Degree			
额定电压/电涌/Rated Voltage(V)/Current(A)		400/20	/
额定脉冲电压(kV)/Rate Impulse Voltage(kV)		4	/
线芯范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)		0.2~2.5/22~14	
间距/Pitch(mm)/螺距范围/Poles		7.5/N=02~12P	
剥线长度/Stripping length(mm)		9~10	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	
标准颜色编号/Standard color number:		PANTONE 428C	

MATERIAL:	/			
MAT NO.:	/			
STATUS:	/			
APPD:				
CHKD:				
DRAWING NO.:	8EDGKGB-7.5-1000-C02			
TYPE:	CUSTOMER DRAWING			
SCALE:	1:1			
REV	ECN	DESCRIPTION	DRAFT	DATE
1	2	3	4	5

NAME:	8EDGKGB-7.5-XXP-11-1001A(H)			
DRAWING NO.:	8EDGKGB-7.5-1000-C02			
TYPE:	CUSTOMER DRAWING			
SCALE:	1:1			
REV	ECN	DESCRIPTION	DRAFT	DATE
1	2	3	4	5

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司