



PITCH RANGE IN MM	NOMINAL DIMENSION RANGE			
	OVER IN MM	OVER IN MM	OVER IN MM	OVER IN MM
TO 6	6	10	30	60
TO 10	10	24	60	100
TO 15	15	30	90	150
TO 20	20	36	120	210
TO 25	25	42	150	270
TO 30	30	48	180	330
TO 35	35	54	210	390
TO 40	40	60	240	450
TO 45	45	66	270	510
TO 50	50	72	300	570
TO 55	55	78	330	630
TO 60	60	84	360	690
TO 65	65	90	390	750
TO 70	70	96	420	810
TO 75	75	102	450	870
TO 80	80	108	480	930
TO 85	85	114	510	990
TO 90	90	120	540	1050
TO 95	95	126	570	1110
TO 100	100	132	600	1170

5	Spring	Stainless Steel		
4	Pin	Copper	Sn Plated	
3	Housing-2	PA66	UL94V-0	
2	Housing-1	PA66	UL94V-0	
1	Cover	PA66	UL94V-0	
ITEM	NAME OF PART	MATERIAL	NOTES	
UL 标准 /UL Standard:	B	C	D	
额定电压/电涌 /Rated Voltage(V)/Current(A)	300/10	/	/	
IEC 标准 /IEC Standard:	III/3	III/2	II/2	
过压类别 /Overvoltage Category/ 污染等级 /Pollution Degree	III/3	III/2	II/2	
额定电压/电涌 /Rated Voltage(V)/Current(A)	130/10	/	/	
额定脉冲电压 (KV) /Rate Impulse Voltage(KV)	2.5	/	/	
线径范围 (硬线和软线) /Wire Range(rigid and flexible)(mm ² /AWG)	0.2~1.5/28~14			
间距 /Pitch(mm) /线距范围 /Poles	3.5/N=02~24P			
剥线长度 /Stripping length(mm)	10			
使用温度范围 /Operating temperature(°C)	-40~+105			
符合 RoHS 环保要求 /Conform to RoHS	Yes			
颜色 /Standard color number:	PANTONE 7534U			
PANTONE	SURFACE: /			

REV	ECN	DESCRIPTION	DRAFT	DATE

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	
NAME:	8EDGKR-3.5-XXP-11-01A(H)
DRAFT:	XieZhp 2020.06.08
CHKD:	
DRAWING NO.:	8EDGKR-3.5-C02
TYPE:	CUSTOMER DRAWING

SIZE:	A4
SCALE:	2:1
SHEET:	1/1
REV:	T0

NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司