



公差等级/General	Tolerances(mm)										0.1/10		
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>280	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~
3	6	10	18	30	50	80	120	180	280	315	400	500	>500
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50
													±Z

ITEM	NAME OF PART	MATERIAL	NOTES
3	Current carrier	Steel	Zn Plated
2	Screws	Steel	Zn Plated
1	Housing	PA66	UL94V-2

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)	300	30	300/710
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	750/76	/
额定冲击电压(kV)/Rate Impulse Voltage(kV)	/	3.0	/
拧紧扭矩(Torque Tightening(N·m/Lb·in))	M4: 1.2/10.53		
导线范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	2.5~16/12~10		
间距/Pitch(mm)/线数范围/Poles	15.0		
剥线长度/Stripping length(mm)	10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
宁波高松电子有限公司

DRAWING NO.: DG15HS-1.2-XXP-1Y-100A(H)
 DFT: WangY1 2020.05.21
 TYPE: CUSTOMER DRAWING
 SCALE: 1:1
 REV T0
 SHEET 1/1

REV	ECN	DESCRIPTION	DFT	DATE
1	2	3	4	5